

## Bath faucet THERMO-10

Product information



### Description

Comfort. Guarantee of stable water temperature. Elegant design, thermo elements of high quality VERNET (France). Safety. Instantaneous hot water shutoff in case of cold water closure prevents from possible burn.

- 5-years warranty
- After assembly all our faucets are being 100% tested
- Durable and glossy surface on all our faucets. We use more durable coating for shine and long-term use of faucets, which is more resistant to scratches, dents, limescale, rust.
- Faucets aerators with a silicone surface prevents the formation of the lime scale and provides a steady stream of water over a long period of time.
- Aerator Eco Neoperl ensures long-lasting, quiet and flawless performance of the faucet.
- High-quality brass with lowered content of harmful impurities is one of the most important component materials.
- Faucets with the ANTI-NOISE system work silently and do not cause discomfort.
- Air and water mixing technology ensures exceptional economy.
- Diverter with the function of an automatic switch and possibility of state fixation.
- Check valve – mostly used for the prevention of impure water backflow to the water supply system.
- Aerator ANTILIME – we use Neoperl® Cascade SLC aerators with a silicone surface, which prevents the formation of the lime scale and provides a steady stream of water over a long period of time. The aerator with the ANTILIME function is easy to maintain,
- Thermo – faucet with the built-in thermostat. Automatically mixes and maintains the set temperature of the water at the outlet. Prevents burns from the hot water in case of cold water pressure drop in the system.



### Specification

Code	H10008
Intended use	Bath faucet
EAN	4779035272008
Warranty	5
Series	Thermo
Segment	Premium
Connection	3/4
Finish	Chrome plated
Debit l/m	12.7

### Components



636719


EAN: 4779035271605



636357

EAN: 4779035274422

## Scheme



## Package



<b>Package quantity</b>	8
<b>Weight Brutto (kg)</b>	2.235
<b>Weight Netto (kg)</b>	1.8815
<b>1 package length (m)</b>	0.09
<b>1 packaging depth (m)</b>	0.313
<b>The primary package width (m)</b>	0.187
<b>2 package weight (kg)</b>	0.7
<b>2 packaging capacity</b>	0.04899
<b>2 Packaging depth (m)</b>	0.375
<b>2 packaging length (m)</b>	0.39
<b>2 packaging width (m)</b>	0.335